

# MIRA<sup>®</sup> 151

Mid-range water-reducing admixture

---

## Product Description

MIRA<sup>®</sup>151 is a mid-range water reducer specifically formulated to produce concretes with enhanced finishing characteristics and controlled set time. It is a ready-to-use liquid admixture with superior dispersing capacity for the cement particles in the concrete mix. This capability exceeds that of normal water-reducing admixtures, resulting in better control.

MIRA 151 contains no added chloride. One litre weighs approximately 1.29kg ± 0.02kg.

MIRA 151 is formulated to comply with the following chemical admixture specifications for concrete: ASTM C494, Type D, Type G; BS 5075: Part 1.

## Applications

Excellent slump control and slump retention are necessary properties of any high quality concrete. MIRA 151 is a tailor-made admixture that helps concrete to achieve excellent slump retention for all ranges of design workability. MIRA 151 is extremely effective in enhancing workability and slump retention even in mid-slump concrete and concrete with manufactured sand (crush granite fines), where conventional admixtures have difficulties achieving these properties

MIRA 151 is suitable for a wide range of quality concrete, from low to higher grade concrete, by adjusting addition rate. The use of Daracem<sup>®</sup> or Darex<sup>®</sup> superplasticiser can help to provide further water reduction when very low water-cement ratio is needed.

## Product Advantages

- MIRA 151 is robust to variation in harmful clay content in manufactured sand or quarry dust, and help accommodate variation in quality of manufactured sand to give consistent quality of concrete.
- Provides long slump life with controlled set times.
- 8-20% water reduction and dispersion characteristics allow the production of lower water-to-cement ratio concretes and more complete hydration.
- Finishes easily without stickiness, tearing or spotty set characteristics, which results in quick and easy application to the concrete mix water for rapid batching.

## Packaging and Storage

MIRA 151 is available in bulk and in 205L drums. MIRA 151 contains no flammable ingredients. In storage, and for proper dispensing, MIRA 151 should be stored under shelter and away from direct sunlight.



## Addition Rates

Addition rates of MIRA 151 can vary with type of application. Depending on the application, dosage rates can range from 300 to 1,000mL / 100kg of cementitious material. At a given watercement ratio, the slump required for placement can be controlled by varying the addition rate. We recommend that trials are conducted beforehand to determine the optimum dose range to suit your application. If further assistance is required please consult your local GCP representative.

## Compatibility with Other Admixtures

Most water reducers or water-reducing retarders are compatible with MIRA 151 as long as they are added separately to the concrete. MIRA 151 is not compatible with polycarboxylatebased admixtures.

## Dispensing Equipment

Please contact your local GCP representative for further information regarding the dispensing equipment for this product

## Health and Safety

See MIRA 151 Material Safety Data Sheet or consult GCP Applied Technologies.

[th.gcpat.com](http://th.gcpat.com) | Thailand customer service: 66 2 030 9700

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

MIRA, Darex and Daracem are trademarks, which may be registered in the United States and/or other countries, of GCP Applied Technologies, Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2017 GCP Applied Technologies, Inc. All rights reserved

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Alpharetta, GA 30009, USA

GCP Applied Technologies Holdings (Thailand) Limited., 848 Moo 2, Bangpoo Industrial Estate (North), Phraksa Mai, Muang Samutprakarn, Samutprakarn 10280, Thailand

This document is only current as of the last updated date stated below and is valid only for use in Thailand. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on [www.th.gcpat.com](http://www.th.gcpat.com). Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2022-01-28

[th.gcpat.com/solutions/products/mira-mid-range-water-reducers/mira-151](http://th.gcpat.com/solutions/products/mira-mid-range-water-reducers/mira-151)