

YTL™ Geotextile Sheet

An auxiliary product designed for drainage applications such as the layering of underground drainage pipes and basement

Product Description

YTL™ Geotextile Sheet is a non-woven, needle punched polypropylene filter fabric. Various grades are available for different applications.

Applications

- Underground drainage
- Car parks
- Bridge abutments
- Green roofs
- Retention bunds
- Grass paved areas
- Tunnel

Physical Properties

PROPERTIES		UNIT					TYPICAL VALUE
		100g /m ²	150g /m ²	200g /m ²	250g /m ²	300g /m ²	
Thickness	mm	≥0.9	≥1.3	≥1.7	≥2.1	≥2.4	
Tensile At Break	KN / m	≥2.5	≥4.5	≥6.5	≥8	≥9.5	
Elongation At Break	%	25-100	25-100	25-100	25-100	25-100	
Tearing Strength	KN	≥0.08	≥0.12	≥0.16	≥0.20	≥0.24	

Test method: GB/T17638-1998

Typical test values may represent average values from samples tested

Product Advantages

- Construction — conforms easily to the ground or trench surface for trouble-free installation.
- Strength — withstands severe installation stresses with high-puncture and burst resistance.
- Filtration — high-permeability properties provide high water flow rates while providing excellent filtration properties.
- Environments — chemically stable in a wide range of aggressive environments.
- Cost-effective — provide economical solutions to many civil engineering applications including a cost-effective alternative to graded aggregate filters.

Supply

UNIT		TYPICAL VALUE				
		100g /m ²	150g /m ²	200g /m ²	250g /m ²	300g /m ²
Roll Size	m	1.78 width x 250 length	1.78 width x 250 length	1.78 width x 250 length	1.78 width x 250 length	1.78 width x 250 length
Roll Weight	kg	44.5	66.75	89	111.25	133.5

Health and Safety

Read the product label and Material Safety Data Sheet (MSDS) before use. Users should acquaint themselves with all risk and safety phrases. MSDS can be obtained from GCP Applied Technologies.

Technical Services

For assistance with working drawings for projects and additional technical advice, please contact GCP Applied Technologies.

th.gcpat.com | Thailand customer service: 66 2 030 9700

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

YTL is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies, Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2016 GCP Applied Technologies, Inc. All rights reserved.

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Alpharetta, GA 30009, USA

GCP Applied Technologies Holdings (Thailand) Limited, 848 Moo 2, Bangpoo Industrial Estate (North), Phraksa Mai, Muang Samutprakarn, Samutprakarn 10280, Thailand

This document is only current as of the last updated date stated below and is valid only for use in Thailand. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.th.gcpat.com. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2025-05-19

th.gcpat.com/solutions/products/ytl-geotextile-sheet